

AQ300L

The masters in linear EDM technology



Linear wire EDM technology at entry level prices

- Anti-electrolytic generator SUPER BS
- Sodick fine corner control SFCC
- Linear glass scales on all axes
- High-speed automatic wire threader AWT
- Fine Measuring Control FMC
- Active Power Restart (UPS)
- Wire end remover
- Voltage stabiliser
- Dielectric Chiller
- Fast LAN networking
- Wire chopper
- Integrated 3D-CAM System

Technical Data

X / Y / Z axis travel (mm)	300 x 200 x 200
U / V axis travel (mm)	80 x 80
Max. workpiece dims (mm)	500 x 300 x 200
Max. workpiece weight (kg)	300
Controlled axes	5
Wire diameter (mm)	ø 0,15 - ø 0,3
Wire tension (N)	3 - 23
Max. wire speed (mm/s)	420
Taper angle at 100 mm height	+/- 20°
Machine installation dimensions	2.400 x 3.750
Machine tool dimensions	1,300 x 2,426 x 2,210
Machine weight (kg)	2,700

CONTACT

Sodick Europe Ltd.
Rowley Drive, Baginton
Coventry, CV3 4LS
United Kingdom
Phone +44(0)2476214314
Fax +44(0)2476305680

Sodick Deutschland GmbH
Zentrale
Robert-Bosch-Str. 30
D - 71106 Magstadt
Phone +49 (0) 71 59 16 76 - 0
Fax +49 (0) 71 59 16 76 - 21

Sodick Contact
E-Mail: europa@sodick.eu.com
Internet: www.sodick.org

Sodick