

AQ75L

The masters in linear EDM technology



Our biggest EDM

- Ceramic table
- Linear glass scales
- Linear motor for the X, Y, and Z axes
- Automatic fire extinguisher
- Cooling system
- SVC Circuit
- SQ Circuit super quality finish
- LAN interface

Technical Data

X / Y / Z axis travel (mm)	700 x 500 x 350
Table dimension (mm)	900 x 750
Worktank dims (mm)	1,100 x 950 x 500
Dielectric level (min - max, mm)	185 - 450
Max. workpiece weight (kg)	2,000
Max. electrode weight (kg)	100
Step resolution (mm)	0.0001
Max. positioning speed (mm/s)	5.0
Table - chuck distance (mm)	300 - 650
Controlled axes	4
Machine weight (kg)	11,000

Optional features

C axis (4 axes controlled)
C axis SE572 (4 axes controlled)
Elektrodenwechsler 4-50 Positionen
RS232C interface
Uninterruptible power supply (UPS)
LAN facility
STP mode for carbide machining

CONTACT

Sodick Europe Ltd.
Rowley Drive, Baginton
Coventry, CV3 4LS
United Kingdom
Phone +44(0)2476214314
Fax +44(0)2476305680

Sodick Deutschland GmbH
Zentrale
Robert-Bosch-Str. 30
D - 71106 Magstadt
Phone +49 (0) 71 59 16 76 - 0
Fax +49 (0) 71 59 16 76 - 21

Sodick Contact
E-Mail: europa@sodick.eu.com
Internet: www.sodick.org

Sodick

